

# CABLE RETENTION

**tyco**



## Metal Cable Tie – Tyco Ball Locking Type 316SS

Tyco's 316 Stainless Steel Ball Locking Cable ties are very quick and easy to use. They are extremely non-corrosive, making them highly suited to aggressive environments, such as marine cable bundling. These marine grade ball lock cable ties are supplied either coated or uncoated to suit the customers requirements.

|               |                     |                     |
|---------------|---------------------|---------------------|
| PERFORMANCE   | Strength            | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ |
|               | Temperature         | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ |
|               | Speed               | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ |
|               | Weathering          | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ |
|               | Chemical            | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ |
| Dynamic Range | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ |                     |

### Applications

- Aerospace
- Automotive Aftermarket
- Chemical Industry
- Electrical and Electronic Industries
- Fixing Identification
- Offshore
- Railway Industry
- Shipyards

### Certifications




### Materials – see section 10.3

- **W5** 316 SS
- On Request
- **W5** 316 SS coated

|             |                     |
|-------------|---------------------|
| Temperature | ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ |
|-------------|---------------------|

### Installation Tools – see section 9.1



MT-MCT-01

| HCL Part No  | Max Diameter inch | Length inch | Band Width inch | Band Thickness inch | Bag Quantity |
|--------------|-------------------|-------------|-----------------|---------------------|--------------|
| BLT-4.6-100  | 0.98              | 3.90        | 0.18            | 0.02                | 100          |
| BLT-4.6-150  | 1.57              | 5.85        |                 |                     |              |
| BLT-4.6-200  | 1.97              | 7.80        |                 |                     |              |
| BLT-4.6-260  | 2.72              | 10.14       |                 |                     |              |
| BLT-4.6-360  | 4.02              | 14.04       |                 |                     |              |
| BLT-4.6-520  | 5.98              | 20.28       |                 |                     |              |
| BLT-4.6-620  | 7.48              | 23.40       |                 |                     |              |
| BLT-4.6-840  | 10.00             | 32.76       |                 |                     |              |
| BLT-4.6-1000 | 11.81             | 39.00       |                 |                     |              |
| BLT-7.9-100  | 6.98              | 3.90        |                 |                     |              |
| BLT-7.9-150  | 1.57              | 5.85        |                 |                     |              |
| BLT-7.9-200  | 1.97              | 7.80        |                 |                     |              |
| BLT-7.9-260  | 2.72              | 10.14       |                 |                     |              |
| BLT-7.9-360  | 4.02              | 14.04       |                 |                     |              |
| BLT-7.9-520  | 5.98              | 20.28       |                 |                     |              |
| BLT-7.9-620  | 7.48              | 24.18       |                 |                     |              |
| BLT-7.9-840  | 10.00             | 32.76       |                 |                     |              |
| BLT-7.9-1000 | 11.81             | 39.00       |                 |                     |              |

All weights, dimensions & quantities are subject to a 2.5% tolerance. To add material selection to the HCL Part No: for W5, add "W5".