

HEAVY DUTY CLAMPS



MECKIND

Preformed Band Clamps

Preformed Band Clamps offer a smooth inner diameter and provide the highest strength capability. They are manufactured in a wide range of fixed diameters and come in 2 types of materials. Vibration resistant and automatically locked with one simple lever movement, these clamps are ideal where superior strength is required. These are often the ideal hose clamping solutions for Hydraulic applications.

PERFORMANCE	Strength	■■■■
	Temperature	■■■■
	Speed	■■■
	Weathering	■■■
	Chemical	■■■
Dynamic Range	■■■■	

Applications

- Agricultural Machinery
- Sewer Cleaning Equipment
- Offshore
- Welding Equipment
- Railway Industry

Materials – see section 10.3

- **W3** 301 SS

On Request

- **W5** 316 SS

Weathering	■■■■
Chemical	■■■■

Installation Tools – see section 9.1



MT-MB-01



MT-MB-02

Both tools are required to install Preformed clamps.

HCL Part No	Max Diameter inch	Band Width inch	Band Thickness inch	Box Quantity			
PC-6-19	0.74	0.25	0.02				
PC-6-21	0.80						
PC-6-25	0.99						
PC-6-35	1.36						
PC-6-38	1.46						
PC-6-51	1.98						
PC-6-63	2.48						
PC-6-70	2.73						
PC-6-76	2.97						
PC-6-90	3.47						
PC-6-102	3.96	0.37	0.03	100			
PC-6-114	4.46						
PC-10-21	0.80						
PC-10-25	0.99						
PC-10-35	1.36						
PC-10-51	1.98						
PC-10-64	2.48						
PC-10-76	2.97						
PC-10-90	3.47						
PC-10-102	3.96						
PC-13-26	0.99	0.50	0.03				
PC-13-32	1.24						
PC-13-38	1.49						
PC-13-45	1.74						
PC-13-51	1.98						
PC-13-64	2.48						
PC-13-70	2.73						
PC-13-76	2.97						
PC-13-90	3.47						
PC-13-102	3.96						
PC-16-38	1.49	0.62	0.03				
PC-16-45	1.74						
PC-16-51	1.98						
PC-16-57	2.23						
PC-16-64	2.48						
PC-19-51	1.98						
PC-19-64	2.48						
PC-19-70	2.73						
PC-19-76	2.97						
PC-19-89	3.47						
PC-19-102	3.96	0.75	0.03	50			
PC-19-114	4.46						
PC-19-127	4.95						
PC-19-133	5.20						
PC-19-152	5.94						
PC-19-165	6.44						
PC-19-178	6.93						
PC-19-203	7.92						
							25

All weights, dimensions & quantities are subject to a 2.5% tolerance.
To add material selection to the HCL Part No: for W3, add "W3"